

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/008929 A1

(51) International Patent Classification⁷: **H04H 5/00,**
H04B 1/16

AA Eindhoven (NL). VAN VALBURG, Christinus, J.
[NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven
(NL).

(21) International Application Number:
PCT/IB2004/051240

(74) Agent: ELEVELD, Koop, J.; Prof. Holstlaan 6, NL-5656
AA Eindhoven (NL).

(22) International Filing Date: 16 July 2004 (16.07.2004)

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03102241.1 21 July 2003 (21.07.2003) EP

(71) Applicant (for all designated States except US): KONIN-
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

(72) Inventors; and

(75) Inventors/Applicants (for US only): TEN PIERICK,
Hendrik [NL/NL]; c/o Prof. Holstlaan 6, NL-5656

[Continued on next page]

(54) Title: RECOVERING A SIGNAL WITHOUT A PHASE LOCKED LOOP



(57) Abstract: An arrangement for recovering a first digital signal (7,31) from a digital input signal (20) comprises a digital filter (29) for filtering the digital input signal (20), a digitally controlled oscillator 28 for generating a digital reference signal (21) and a digital phase detector (22) for determining a phase difference (25) between the filtered digital input signal (27) and the digital reference signal (21). The first digital signal (7, 31) can be recovered by adding the determined phase difference (25) to the phase of the digital reference signal (21).

WO 2005/008929 A1

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments